PASS QUESTION

PRACTICE QUESTIONS

EXAM PREPARATION GUIDE

Learn Smarter

Practice Effectively

Achieve Your Goals

https://www.passquestion.com

One Year of Content Updates Included

Exam : **EX362**

Title : Red Hat Certified Specialist in Identity Management exam

Version : DEMO

1.You must deploy a brand-new IdM realm using scripts on RHEL 9. Use integrated DNS and set Google Public DNS as a forwarder. Primary server: ipa1.example.com (10.10.10.11). Realm: EXAMPLE.COM, domain: example.com. Ensure services start at boot and verify the install.
A. See the Explanation.
Answer: A
Explanation:
1. Set hostname and basic resolution: hostnamectl set-hostname ipa1.example.com
echo "10.10.10.11 ipa1.example.com ipa1" >> /etc/hosts
2. Open firewall and install packages:
dnf -y install ipa-server ipa-server-dns firewall-cmd --add-service={freeipa-ldap,freeipa-ldaps,dns} --permanent firewall-cmd --reload
3. Run unattended install with integrated DNS: ipa-server-install -U \
--realm EXAMPLE.COM --domain example.com \ --hostname ipa1.example.com \
--setup-dns --forwarder=8.8.8.8 \ --admin-password 'RedHat123!' \ --ds-password 'RedHat123!'
4. Enable KRA (optional but commonly expected): ipa-kra-install -p 'RedHat123!'
5. Enable/verify services:
systemctl enable --now ipa
kinit admin
ipa ping
6. Validate DNS SRV and A records resolve: dig +short _ldap._tcp.example.com SRV dig +short ipa1.example.com A

2.Install the same IdM primary using Ansible Automation Platform (AAP) and the freeipa.ansible_freeipa collection, with integrated DNS and a forwarder.
A. See the Explanation.
Answer: A
Explanation:
1. On the control node, install the collection:
ansible-galaxy collection install freeipa.ansible_freeipa
2. Create inventory inventory.ini: [ipaservers] ipa1.example.com
[all:vars]
ansible_user=root
3. Create install-ipa.yml:

- hosts: ipaservers
become: true collections:
- freeipa.ansible_freeipa roles:
- role: ipaserver
state: present
ipaserver_domain: example.com
ipaserver_realm: EXAMPLE.COM
ipaserver_setup_dns: true ipaserver_forwarders:
- 8.8.8.8
ipaserver_admin_password: "RedHat123!"

ipaserver_dirman_password: "RedHat123!"
ipaserver_setup_kra: true
4. Run:
ansible-playbook -i inventory.ini install-ipa.yml
5. Post-check: kinit admin ipa config-show
ipa dnsconfig-show

3.Install an IdM server with external DNS (no integrated DNS). Configure global DNS forwarders afterwards from IdM.
A. See the Explanation.
Answer: A
Explanation:
1. Install IdM server without DNS: dnf -y install ipa-server ipa-server-install -U \
--realm EXAMPLE.COM --domain example.com \ --hostname ipa1.example.com \
--no-dns --admin-password 'RedHat123!' --ds-password 'RedHat123!'
2. Ensure external DNS has A/PTR and SRV records for IdM. At minimum (add in your external DNS):
ipa1.example.com. A 10.10.10.11
_kerberos._udp.example.com. SRV 0 100 88 ipa1.example.com. _kerberos._tcp.example.com. SRV 0 100 88 ipa1.example.com. _kpasswd._udp.example.com. SRV 0 100 464 ipa1.example.com. _ldap._tcp.example.com. SRV 0 100 389 ipa1.example.com.
3. From IdM, set resolvers and forwarders (affects client-side DNS info served by SSSD/DNS discovery only if DNS integrated; otherwise for Kerberos discovery rely on SRV you created):
ipa config-mod --dns-forwarders=1.1.1.1 --dns-forwarders=8.8.8.8
4. Validate realm and KDC discovery:
ipa ping
5. Confirm clients can discover via SRV (from a client host): dig +short _ldap._tcp.example.com SRV

4.Perform a CA-less IdM deployment using an external corporate CA. Complete the two-stage process.
A. See the Explanation.
Answer: A
Explanation:
1. Stage 1: generate CSR: dnf -y install ipa-server
ipa-server-install --realm EXAMPLE.COM --domain example.com \
--hostname ipa1.example.com \
--no-ntp --external-ca -U \
--admin-password 'RedHat123!' --ds-password 'RedHat123!'
2. Collect CSR files (commonly /root/ipa.csr); submit to your external CA to obtain the server cert and the CA chain (PEM).
3. Stage 2: complete the install by providing the certs:
ipa-server-install --external-cert-file=/root/ipa_server_cert.pem \ --external-cert-file=/root/ca_chain.pem -U
4. Start/enable and verify: systemctl enable --now ipa kinit admin
ipa cert-show 1

5.Enroll a RHEL client app1.example.com into the IdM realm, configure SSSD, and verify identity and sudo data retrieval.
A. See the Explanation.
Answer: A
Explanation:
1. Client prep:
hostnamectl set-hostname app1.example.com
echo "10.10.10.11 ipa1.example.com ipa1" >> /etc/hosts dnf -y install ipa-client sssd oddjob-mkhomedir
2. Run client install (use your server FQDN):
ipa-client-install -U --domain example.com --server ipa1.example.com \
--realm EXAMPLE.COM --mkhomedir --principal admin --password 'RedHat123!'
3. Validate identity lookup: getent passwd admin
id admin
4. Validate Kerberos and sudo: kinit admin
sudo -l
5. Ensure SSSD enabled: systemctl enable --now sssd